




LUMENS / <i>Lumens</i>	fino a / up to
EFFICIENZA / <i>efficiency</i>	102 lm/w - 94 lm/w
COLLEGAMENTO / <i>Wiring</i>	ECG
TEMPERATURA COLORE / <i>CCT</i>	
INDICE RESA CROMATICA / <i>CRI</i>	
STRUTTURA / <i>Housing</i>	Nylon rinforzato / <i>reinforced nylon</i>
SCHERMO / <i>Diffuser</i>	Policarbonato opale autoest. / <i>opal polycarbonate self exting</i>
LENTI / <i>Lences</i>	
DISTRIBUZIONE / <i>light distribution</i>	diretta 160° / <i>direct 160°</i>
COLORI / <i>Colours</i>	Bianco, Nero, Grigio / <i>White, Black, Grey</i>
VERNICIATURA / <i>Paint</i>	



lumen	CCT	potenza	Dimensioni	Peso
(lm)	(K)	(W)	(mm)	(kg)
1790			110X270X150	0,45

			IP 55	IK 09	GARANZIA 5 ANNI		240V 50-60 HZ			MADE IN ITALY
--	--	--	-------	-------	--------------------	--	------------------	--	--	---------------

Schede tecniche complete varianti disponibili su [www.mgilluminazione.it](http://www.mgilluminazione.it)