



LUMENS / <i>Lumens</i>	fino a / up to 4000
EFFICIENZA / <i>efficiency</i>	111lm/W@700mA
COLLEGAMENTO/ <i>Wiring</i>	ECG / DALI a richiesta
TEMPERATURA COLORE / <i>CCT</i>	3000-4000 K
INDICE RESA CROMATICA / <i>CRI</i>	> 80
STRUTTURA / <i>Housing</i>	Alluminio / Aluminium
GRIGLIA / <i>Diffuser</i>	PMMA metall. + pc TRASP./Metall. PMMA+Trasp. PC
DISTRIBUZIONE / <i>light distribution</i>	Diretta / Direct
FINITURA / <i>Finish</i>	Bianco RAL 9003/ <i>White Ral 9003</i>



lumen (lm)	CCT (K)	potenza (W)	Dimensioni (A) (mm)	Peso (kg)
3140	3000	30	595x595x25	3,50
3300	4000	30	595x595x25	3,50
3600	3000	36	595x595x25	3,50
4000	4000	36	595x595x25	3,50
3140	3000	30	145x1195x90	2,50
3300	4000	30	145x1195x90	2,50
3600	3000	36	145x1195x90	2,50
4000	4000	60	145x1195x90	2,50
1570	3000	15	318x330x30	2,50
1650	4000	15	318x330x30	2,50
1900	3000	19	318x330x30	2,50
2000	4000	19	318x330x30	2,50

LED	ECG		IP 20	IK	GARANZIA 5 ANNI		110-240V 50-60 HZ			
-----	-----	--	-------	----	--------------------	--	----------------------	--	--	--

Schede tecniche complete varianti disponibili su [www.mgilluminazone.it](http://www.mgilluminazone.it)